

# KFX-81TK2

### **Product Data Sheet**

### Flux Cored Wire for Low Alloy Steel

| Specification   | AWS A5.29 E81T1-K2C   |
|-----------------|---|
| Applications    | <ul> <li>Capable of producing weld deposits with tensile strength exceeding 590 N/mm<sup>2</sup></li> <li>Used in off-shore and similar applications</li> </ul> |
| Characteristics | <ul> <li>Superior impact properties at low temperature.</li> <li>Stable arc, less spatters, smooth weld beads and good weldability.</li> </ul>                  |
| Note on Usage   | <ul> <li>Preheat Temperature: 135-165°C</li> <li>Interpass temperature: 135-165°C</li> </ul>  |

# **Mechanical Properties & Chemical Composition of All Weld Metal**

### **Welding Conditions**

# 45° 20 Unit: mm

[Joint Preparation & Layer Details]

### **Method by AWS Rules**

| Diameter(mm)                   | 1.2mm                |
|--------------------------------|----------------------|
| Shielding Gas                  | 100% CO <sub>2</sub> |
| Flow Rate (I/min)              | 20                   |
| Amp / Volt                     | 280 / 32             |
| Stick-Out (mm)                 | 15-20                |
| Interpass Temp ( $^{\circ}$ C) | 150±15               |
| Polarity                       | DC(+)                |

Rev:1 Date: 20170228

### Mechanical Properties of the Weld Metal

| Brand Name | Tensile Test Results |            |         | Charpy V      | -Notch Imp<br>(Joules) | act Value |
|------------|----------------------|------------|---------|---------------|------------------------|-----------|
|            | Y.S. (MPa)           | T.S. (MPa) | EL. (%) | <b>-30</b> °ℂ | -40°C                  | -60°C     |
| KFX-81TK2  | 603                  | 640        | 24      | 151           | 132                    | 83        |
| E81T1-K2C  | 470 min.             | 550–690    | 19min   | 27 min        | -                      | -         |

### • Chemical Analysis of the Weld Metal

Unit: wt%

| Brand Name | С     | Si   | Mn       | Р     | S     | Ni      | Cr    | Мо    | V     |
|------------|-------|------|----------|-------|-------|---------|-------|-------|-------|
| KFX-81TK2  | 0.04  | 0.40 | 1.38     | 0.020 | 0.008 | 1.297   | 0.026 | 0.003 | 0.007 |
| E81T1-K2C  | ≤0.15 | ≤0.8 | 0.5-1.75 | ≤0.03 | ≤0.03 | 1.0-2.0 | ≤0.15 | ≤0.35 | ≤0.05 |

### **Diffusible Hydrogen Content of Weld Metal**

Unit: ml/100g weld metal

|              |     |     | •   |  |
|--------------|-----|-----|-----|--|
| Specimen no. | 1   | 2   | 3   |  |
|              | 5.2 | 5.1 | 5.4 |  |

<sup>\*</sup> Test method: carrier gas hot extraction with infrared furnace; conforms to EN/ISO 3690 and AWS A4.3.

## **Available Sizes and Suggested Operating Range**

| Welding     | Wire Diameter (mm) |         |         |  |
|-------------|--------------------|---------|---------|--|
| Position    | 1.2mm              | 1.4mm   | 1.6mm   |  |
| F&HF        | 120~300            | 150~350 | 180~400 |  |
| Vertical Up | 200~260            | 220~270 | 230~280 |  |

This information is provided solely for the purpose of confirming product conformance with applicable standards. The serviceability of a product or structure utilizing this type of information is and must be the sole responsibility of the builder/user. Many variables beyond the control of Kuang Tai Metal IND CO., LTD. affect the results obtained in applying this type of information. These variables include, but are not limited to, welding procedure, shielding gas, plate chemistry and temperature, weldment design, fabrication methods and service requirements.

Rev:1 Date: 20170228